

M70		
Specifications.	Values	Notes / Comments.
Nominal system impedance	4 ohm	(Z-min 3.6 ohm)
Frequency response	80-20Khz	(average response in room +/- 2dB)
Frequency roll off	80 Hz	(-10dB 80 Hz near field w all mounted)
Crossover frequency	1.8 Khz	"Phase focused" (4th&2nd order)
Tweeter (shielded)	1" Dome	Coated silk dome / Neodymium magnet
Woofers (shielded)	2 x 4"	Coated glass fibre
Power handling	125 watt	Long term IEC-268-5 (cycled input 80-20Khz)
Power handling	70 watt	Rated IEC-268-5 (constant input 80-20Khz)
Recommended amp power	25-200 watt	(Recommended amp power to drive speaker)
Sensitivity	89 dB	Average SPL 2.83V/ 1mtr (on axis 200-10KHz)
System principle		Sealed enclosure
Connection	Terminal gold plating	Screw for 5 mm cable / Banana
Accessories	Yes	Wall mount brackets/screws/gloves
Welcome card	Yes	"Included in packing"
Finish		Black / white Satin
Dimensions	H x W x D	18,1 x 5,1 x 3,3 inch 46 x 13 x 8,8 cm (incl grill)
Weight		8.4 lb / 3,80 kg
	Version 1 Aug 2019	