

<b>S150T</b>		
<b>Specifications.</b>	<b>Values</b>	<b>Notes / Comments.</b>
Nominal system impedance	4 ohm	(Z-min 3.4 ohm)
Frequency response	80-20Khz	(average response in room +/- 3dB)
Frequency roll off	80 Hz	(-6dB 80 Hz near field)
Crossover frequency	1.5Khz	"Phase focused" (4th&2nd order)
Front Tweeter	1,1" Dome	Coated silk dome / Low compression
Front Woofer	5.25"	Coated Glass Fibre
Side drivers	2 x 3.25"	Polymer coated Textured Paper
Power handling	100 watt	Long term IEC-268-5 (cycled input 80-20Khz)
Power handling	50 watt	Rated IEC-268-5 (constant input 80-20Khz)
Recommended amp power	25-200 watt	(Recommended amp power to drive speaker)
Sensitivity	85dB	Average SPL 2.83V / 1mtr (on axis 200-10KHz)
System princip		Sealed enclosure
Connection	Terminal gold plating	Screw for 6 mm cable / Banana
Accessories	Yes	Wall mount brackets/screws/gloves/rubber feets
Welcome Card	Yes	"Included in packing"
Finish		Black satin
Dimensions	H x W x D	10.5x8x6.5 inch - 26.7x20.3x16.5 cm
Weight	Netto	10.25 lb / 4.6 kg
	Version 1. Feb 2019.	